

Stoneworld Wood Data Sheet & Installation Guide

SPECIFICATION

Thickness of Birch Ply:	14.5mm
Thickness of Oak:	6mm
Profiled Edge:	Tongue & Groove on 4 sides & Micro Bevel on Long Edge
Board Lengths:	2.2m – 2.4m Long
Board Widths Available:	180mm or 220mm

PACK SIZES

WOOD WIDTH & LENGTH	AREA PER PACK
180mm Width, 2.2m Length Boards	1.584 Sq. Metres
180mm Width, 2.4m Length Boards	1.728 Sq. Metres
220mm Width, 2.2m Length Boards	1.936 Sq. Metres
220mm Width, 2.4m Length Boards	2.112 Sq. Metres

PLEASE NOTE: TUDOR WOOD FINISHES MINIMUM 50m² ORDER

FINISHES & AVAILABLE WIDTHS

WOOD FINISH	WIDTHS AVAILABLE
Aged Unfinished	180mm or 220mm
Brushed & Oiled	180mm or 220mm
Brushed & White Oiled	180mm or 220mm
Light Smoked	180mm Only
Dark Smoked	180mm Only
Tudor (8 Colours Available)	220mm Only

FURTHER COLOUR OPTIONS ARE AVAILABLE USING BESPOKE COLOURED OILS IN SITU

INSTALLATION SUTABILITY (UNDERLAY)

Over Screed including underfloor heating
Over Joists with tray style including underfloor heating
Over Concrete
Over Wood
Over Chipboard

METHODS OF INSTALLATION

Floating Floor over underlay – **Must use Heatflow Underlay**
Secret nailing to wood/joists
Part glued – using cartridge glue gun
Fully bonded/ glued – using suitable glue

MAINTENANCE

Brush/Hoover
General Clean with damp cloth
Steam Mop – Apply with Caution
Re-Dressing with Oils (Osmo Oil recommended) – Applied with Brush, Roller or Buffing Machine