




TECHNICAL DATA SHEET

OAK WOOD INTERIOR FLOORING PRODUCT

PRODUCT IDENTIFICATION	
	Commercial Designation: Arden Oak Flooring
	Description: Oak veneer flooring suitable for interior use Colours: Blond HF Sand Flax Jute Maple Tobacco Clay Hazelnut HF Smoke 
	Material: oak veneer over birch ply
	Origin: EU
	High quality oak board flooring from sustainable European forests. Arden Oak Flooring is soft to the touch with a subtle grain achieved with nylon bristle brush character to range.
European Standards: Adhering to EUTR No. 995/2010 This ensures a commitment to using stable hardwoods from sustainable European forests, and extremely low VOC glues, with a high consideration to the environment & safety.	
Stoneworld Oxfordshire Ltd Views Farm, Great Milton, OX44 7NW	
Thickness of Birch Ply	14.5mm
Thickness of Oak:	6mm
Profiled Edge	Tongue & Groove on 4 sides & Micro Bevel on Long Edge
Board Length:	2.2m-2.4m Long
Board Widths Available:	180 or 220mm
Pack Sizes	
WOOD WIDTH & LENGTH	AREA PER PACK
180mm Width, 2.2m Length Boards	1.584 Sq. Metres
180mm Width, 2.4m Length Boards	1.728 Sq. Metres
220mm Width, 2.2m Length Boards	1.936 Sq. Metres
220mm Width, 2.4m Length Boards	2.112 Sq. Metres
PLEASE NOTE: **** WOOD FINISHES MINIMUM 50m2 ORDER	
Installation Suitability (Underlay)	
Over Screed including underfloor heating Over Joists with tray style including underfloor heating Over Concrete Over Wood Over Chipboard	
Methods of Installation	
Floating Floor over underlay- Must use Heatflow underlay. Secret nailing to wood/joists Part glued – using cartridge glue gun. Fully bonded/ glued – using suitable glue.	
Maintenance	
Brush or Hoover General Clean with a damp cloth Steam Mop-Apply with Caution Redressing with oils (Osmo Oil recommended)- Applied with Brush, roller or buffing machine.	