

TECHNICAL DATA SHEET

OAK WOOD INTERIOR FLOORING PRODUCT

PRODUCT IDENTIFICATION	
	Commercial Designation: Charlecote Oak Flooring
	Description: Oak veneer flooring suitable for interior use Colours: Natural Blond Blond HF Tawny Tobacco Mahogany Maple 
	Material: oak veneer over birch ply
	Origin: EU Long lasting oak board flooring that retain their colours and appearance over the years. Charlecote Oak flooring has a subtly revealed grain achieved with gentle brushing. This range has a smaller format, suitable for laying wood floors in a herringbone pattern.
European Standards: Adhering to EUTR No. 995/2010 This ensures a commitment to using stable hardwoods from sustainable European forests, and extremely low VOC glues, with a high consideration to the environment & safety.	
Stoneworld Oxfordshire Ltd Views Farm, Great Milton, OX44 7NW	
Thickness of Birch Ply	14.5mm
Thickness of Oak:	6mm
Profiled Edge	Tongue & Groove on 4 sides & Micro Bevel on Long Edge
Board Length:	600mm Long
Board Widths Available:	120mm wide
Pack Sizes	
WOOD WIDTH & LENGTH	AREA PER PACK
120mm x 600mm for herringbone pattern	
PLEASE NOTE: **** WOOD FINISHES MINIMUM 50m2 ORDER	
Installation Suitability (Underlay)	
Over Screed including underfloor heating Over Joists with tray style including underfloor heating Over Concrete Over Wood Over Chipboard	
Methods of Installation	Maintenance
Floating Floor over underlay- Must use Heatflow underlay. Secret nailing to wood/joists Part glued – using cartridge glue gun. Fully bonded/ glued – using suitable glue.	Brush or Hoover General Clean with a damp cloth Steam Mop-Apply with Caution Redressing with oils (Osmo Oil recommended)- Applied with Brush, roller or buffing machine.