




## TECHNICAL DATA SHEET

### OAK WOOD INTERIOR FLOORING PRODUCT

PRODUCT IDENTIFICATION	
	<b>Commercial Designation: Eathorpe Oak Flooring</b>
	<b>Description:</b> Oak veneer flooring suitable for interior use <b>Colours:</b> Blond HF   Flax   Jute   Umber   Driftwood   Scandi HF   Hickory   Walnut 
	<b>Material: oak veneer over birch ply</b>
	<b>Origin: EU</b> Long lasting oak board flooring that retain their colours and appearance over the years. Eathorpe Oak flooring has a very stylish 'industrial' finish that works well in contemporary schemes. The grain is visible plus a cross-grain pattern is a specific feature of this range.
<b>European Standards:</b> Adhering to EUTR No. 995/2010 This ensures a commitment to using stable hardwoods from sustainable European forests, and extremely low VOC glues, with a high consideration to the environment & safety.	
	
<b>Stoneworld Oxfordshire Ltd</b> <b>Views Farm, Great Milton, OX44 7NW</b>	
<b>Thickness of Birch Ply</b>	<b>14.5mm</b>
<b>Thickness of Oak:</b>	<b>6mm</b>
<b>Profiled Edge</b>	<b>Tongue &amp; Groove on 4 sides &amp; Micro Bevel on Long Edge</b>
<b>Board Length:</b>	<b>2.2m-2.4m Long (560mm for herringbone)</b>
<b>Board Widths Available:</b>	<b>140 or 180 mm</b>
<b>Pack Sizes</b>	
<b>WOOD WIDTH &amp; LENGTH</b>	<b>AREA PER PACK</b>
140mm Width, 560mm Length (herringbone) 180mm Width, 2.2m Length Boards 180mm Width, 2.4m Length Boards	1.584 Sq. Metres 1.728 Sq. Metres
<b>PLEASE NOTE: **** WOOD FINISHES MINIMUM 50m2 ORDER</b>	
<b>Installation Suitability (Underlay)</b>	
Over Screed including underfloor heating Over Joists with tray style including underfloor heating Over Concrete Over Wood Over Chipboard	
<b>Methods of Installation</b>	<b>Maintenance</b>
Floating Floor over underlay- Must use Heatflow underlay. Secret nailing to wood/joists Part glued – using cartridge glue gun. Fully bonded/ glued – using suitable glue.	Brush or Hoover General Clean with a damp cloth Steam Mop-Apply with Caution Redressing with oils (Osmo Oil recommended)- Applied with Brush, roller or buffing machine.